Aluminium Bi-Folding Doors **Enquiry Form**

rour Details		
I am a Homeown	ner Trade Customer	Collect Deliver Required Date (week)
Name		Delivery Address
Company		
Address		Post Code
		Delivery Contact
		Delivery Telephone
Post Code		Customer Ref
Tel/Mobile		Customer Order No
Email		Project Type: New build Refurbishment
Windows and doors installed from 15/06/22 will be subject to revised building regulations. It is the installer's responsibility to ensure that the products are compliant with the regulations for whose the will be installed. For more information with the regulations of the products are compliant with the regulations.		
for where they will be installed. For more information visit www.quickslide.co.uk/blog/guides/2022-changes-to-building-regulations-for-doors-and-windows/		
Door Specifica	ation	
Quantity	Sliding Direction External view	Glazing Sash Options Glazed options come with Argon Gas and
Location	From the left	Toughened Glass as standard Curved Sash Unglazed
) A C	From the right Door Opens	Double Glazed 1.6Wm²K/C'DSER
Width	Inwards	Double Glazed, Laminated 1.6W/m²K/°C' DSER 1.6W/m²K/°C' DSER
Height	Outwards	Triple Glazed
Door Configuration Code	Threshold Standard 50mm	1.3W/m²K Triple Glazed, Laminated
	Low threshold 20mm Low threshold w. ramp 20mm	1.4W/m²K Obscure Glass Square Sash
Door Colour External	Handle Colour	In addition to glazed option Longer lead time applies
White Grey	White	Stipple
Black	☐ Black ☐ Chrome	Other:
Door Colour Internal White	Anthracite Grey Satin Chrome	Spacer Bar Colour
To Match External	Magnetic Door Catch	White Grey
Trickle Vents From the 15/06/2022, the B	White	Black 74.5
Regs state that trickle vents a required on practically all gla elements. Unless otherwise s	are DidCK	Integral Blinds Threshold Options
will include trickle vents in pre-determined locations as:	standard. Satin Chromo	Colour of outer casing: Standard Threshold:
On bi-folding doors, trickle verifitted into a 42mm add-on abouter door frame. If a certain	ents are bove the	Colour of blinds:
'equivalent area' is required, include instructions.	please No sill	
If trickle vents are not require tick below. Please note trickle	red, please 150mm	Frame Extenders (Add-ons)
cannot be retro-fitted. Trickle Vents not requir	190mm	42mm (required with trickle vents)
		Left Right LowThreshold:
	PAS 24 Security Upgrade Laminated glass also required	Top 77.5
	90° Restrictors	Midrail (white/grey only)
Comments:	Illustration (External View):	Mildrail (Willte/grey only)
		Low Threshold Ramp:
		30
		9
		35

Tel: 0844 5610 623 | **Fax:** 0844 5610 624

Email: sales@quickslide.co.uk

Heaton Estate, Bradford Road, Brighouse, West Yorkshire, HD6 4BW

