Aluminium Single & French Doors Enquiry Form

Your Details		Project Details		
I am a Homeowner Trad	Homeowner Trade Customer		Collect Deliver Required Date (week)	
Name		Delivery Address		
Company Address				
Address		Post Code		
		Delivery Contact		
Post Code		Delivery Telephone		
Tel/Mobile		Customer Ref Customer Order No		
Email		Project Type: New build	Refurbishment	
Windows and doors installed from 15/06/	/22 will be subject to revised building regulations	. It is the installer's responsibility to ensure	e that the products are compliant with the regulations	
for where they will be installed. For more information visit www.quickslide.co.uk/blog/guides/2022-changes-to-building-regulations-for-doors-and-windows/				
Door Specification				
Quantity	Threshold Standard 50mm	Glazing Glazed options come with Argon Gas and Toughened Glass as standard	Sash Options Curved Sash	
Location	Low threshold 20mm Low threshold w. ramp 20mm	Unglazed Double Glazed		
Width	Handle Colour	1.6W/m²K/'C' DSER Double Glazed, Laminated		
Height	☐ White ☐ Black	1.6W/m²K/'C' DSER Triple Glazed	M: ACDV23 C: ACDV23 C: ACDV28 C: ACD	
Dear Time	Chrome Anthracite Grey	1.3W/m²K		
Door Type Single	Satin Chrome	Triple Glazed, Laminated	74.5	
French Hinge Side - Single Doors only	Sill No sill	Obscure Glass In addition to glazed option Satin	Square Sash Longer lead time applies	
Viewed externally	85mm 150mm	Stipple		
Right	190mm	Other:		
Door Opens Inwards	225mm	Spacer Bar Colour	M: ACDV23 C: ACDV25 C: ACDV25	
Outwards	PAS 24 Security Upgrade Laminated glass also required	White Grey		
Door Colour External White	90° Restrictors	Black	74.5	
Grey Black	Midrail (white/grey only) Trickle Vents	Integral Blinds Colour of outer casing:	Threshold Options Standard Threshold:	
Door Colour Internal	From the 15/06/2022, the Building Regs state that trickle vents are		T (E)	
White To Match External	required on practically all glazing elements. Unless otherwise specified we will include trickle vents in	Colour of blinds:	S ACMOSOZA	
To Materi External	pre-determined locations as standard. On aluminium doors, trickle vents are fitted into a 42mm add-on above the	Frame Extenders (Add-ons)	ACDVIS ACDVIS	
	outer door frame. If a certain rate of 'equivalent area' is required, please include instructions.	20mm 42mm (required with trickle vents)	70	
	If trickle vents are not required, please tick below. Please note trickle vents	Left Right	Low Threshold:	
	cannot be retro-fitted. Trickle Vents not required	Тор	77.5	
		Bottom		
Comments:	Illustration (External View):			
			Low Threshold Ramp:	
			30	
			186	
			35	

Tel: 0844 5610 623 | **Fax:** 0844 5610 624

Email: sales@quickslide.co.uk

Heaton Estate, Bradford Road, Brighouse, West Yorkshire, HD6 4BW

