

Aluminium Heritage Doors

Enquiry Form

Your Details		Project Details	
I am a	Homeowner <input type="checkbox"/> Trade Customer <input type="checkbox"/>	Collect	<input type="checkbox"/> Deliver <input type="checkbox"/> Required Date (week) <input type="text"/>
Name	<input type="text"/>	Delivery Address	<input type="text"/>
Company	<input type="text"/>		<input type="text"/>
Address	<input type="text"/>	Post Code	<input type="text"/>
	<input type="text"/>	Delivery Contact	<input type="text"/>
Post Code	<input type="text"/>	Delivery Telephone	<input type="text"/>
Tel/Mobile	<input type="text"/>	Customer Ref	<input type="text"/>
Email	<input type="text"/>	Customer Order No	<input type="text"/>
		Project Type:	New build <input type="checkbox"/> Refurbishment <input type="checkbox"/>

Please note, windows and doors are subject to Building Regulations. The regulations changed in 2022 and it's the installer's responsibility to ensure the products are compliant for their intended use where they're installed. Use our specification tool available at www.quickslide.co.uk/requirement-calculators/ to help you understand the product specification required to comply.

Door Specification

Quantity

Location

Width (max 900mm per sash)

Height (max 2155mm)

Door Colour External

Black
 Grey
 White

Door Colour Internal

To Match External
 White

Special colours available upon request, min. order quantity applies.

Door opens

Inwards
 Outwards

Handle Colour

Standard Lever Handle

White
 Black
 Chrome
 Anthracite Grey
 Brushed Chrome

Art Deco Handle

Antique Brass
 Satin Nickel

Sill

No sill
 85mm
 150mm
 180mm

Glass

28mm Double Glazed
 Double Glazed, Laminated

Spacer Bar Colour

Black

Frame Extenders

20mm
 42mm (required with trickle vents)

Left
 Right
 Top
 Bottom

Trickle Vents

Flush Vents
 Link Vents

From the 15/06/2022, the Building Regs state that trickle vents are required on practically all glazing elements. Unless otherwise specified we will include trickle vents in pre-determined locations as standard. On aluminium doors, trickle vents are fitted into a 42mm add-on above the outer door frame. If a certain rate of 'equivalent area' is required, please include instructions.

If trickle vents are not required, please tick below. Please note trickle vents cannot be retro-fitted.






Trickle Vents not required

PAS 24 Upgrade







Couplers

Door Configuration

Configurations Explained - all illustrations are viewed from the outside.

 Double Door
 Single Door (Left Hung)
 Single Door (Right Hung)
 Fixed Frame (Non-opening)
 Top Hung Window

Common Styles

Side- and Top Lights

Side Lights
 Top Light

Draw Your Own

Please include side and top lights if required.

Include horizontal and vertical bars as well as dimensions (mm) to determine bar locations if not equal spacing.

Please note that all horizontal bars will be 48mm transoms and vertical bars will be 25mm astragal bars.

Special Instructions: