




LegacyTM

uPVC Sliding Sash Windows

Operations and Maintenance Manual

QUICK SLIDE
WINDOWS & DOORS

Tel: 0844 5610 623 Email: sales@quickslide.co.uk
Heaton Estate, Bradford Road, Brighouse, West Yorkshire, HD6 4BW

Sash Slide Operation



To operate the sash window, start by unlocking the sashes. Simply lock and unlock the sashes by turning the lever side to side.

Ensure sashes are correctly aligned before operating the sash lock.



Non-locking restrictor



Locking restrictor

If your window is fitted with restrictors, press the restrictor inwards to override the mechanism and allow the sash to open further.

For locking restrictors, use an Allen key to lock the restrictor in either the open or closed position.

For non-locking restrictors, simply push the restrictor in or out to switch between the open and closed positions.



Use lift hooks to open the bottom sash slightly. Push from the centre or with equal force on both sides if your window is not fitted with lift hooks.



Push the bottom sash upwards. To close, simply push the sash down until you hear a click signalling the sash is in place.



The bottom sash does not need to be lifted to operate the top sash.

Bottom Sash Tilt Operation



Use the lift hooks to lift the bottom sash slightly.

Do not attempt to tilt the sash if it's been lifted all the way to the top.

You should now be able to tilt the sash by pushing both the sash buttons inwards and carefully pulling it towards you.

The sash will stay in a secure position when tilted and you do not need to support it.

To close the bottom sash push the sash into its upright position and slide it to the bottom.

If both sashes are tilted in, you will have to push the top sash back into an upright position first, then the bottom sash.

You will hear a clicking sound when the sash has been pushed into its upright and secure position.

Top Sash Tilt Operation



To tilt the top sash, the bottom sash must already be tilted.

Pull the top sash down.

You should now be able to tilt the sash by pushing both the sash buttons inwards and carefully pulling it towards you.

The sash will stay in a secure position when tilted and you do not need to support it.

To close the top sash push the sash into its upright position and slide it to the top.

If both sashes are tilted in, you will have to push the top sash back in up right position first followed by the bottom sash.

You will hear a clicking sound when the sash has been pushed into its upright and secure position.

Please note the top sash will not be able to tilt if the finish on the external and internal side are different. e.g. dual foils or foiled external & smooth PVC internal.



Maintaining the Window

Part / Component	Maintenance
Profile (PVC)	The cleaning interval should be determined by the amount of soiling and should not exceed six months between cleaning. Wipe down with soapy water once every 6 months.
Woodgrain lamination	The cleaning interval should be determined by the amount of soiling and should not exceed six months between cleaning. Wipe down with soapy water once every 6 months. Please do not use solvent cleaners.
Glass units	Clean as necessary with soapy water
Colour coating	The applied coating must be cleaned when it becomes soiled. The cleaning interval should be determined by the amount of soiling and not exceed six months between cleaning. Cleaning should commence at the date of installation using a mild detergent and warm water on all surfaces and a soft cloth or sponge but nothing harsher than a natural bristle brush, followed by freshwater rinsing. Please do not use solvent cleaners.
Balance mechanism	Constant force and lubricating with silicone spray.
Locking mechanisms, handles and additional hardware	Clean with warm soapy water, other proprietary cleaners may affect the paint/lacquer finish and cause flaking and/or discolouration. Wipe handles and aesthetic hardware down once a month.
Sliding, Tilting and Opening Mechanisms	Lubricate once every 6 months. Windows should be operated once every 3 months. Keep visible track surfaces free of contaminants and debris.
Stainless steel tilt arms	The windows must be operated once per month. Lubrication once every 6 months
Galvanised steel products	None required

Please note we deliver our windows and doors with a protective film (tape) to protect them during delivery, handling, and from debris during the installation.

The protective film must be removed immediately upon completion of installation. If the film is left on the product for an extended period of time and is exposed to the heat of the sun, the film will essentially “melt” on to your window and door profiles and will be very difficult to remove and there is a high risk of damage to the window and door finish.